

Athena Bulkhead LED Instructions

IMPORTANT INSTALLATION INFORMATION This product must be installed in accordance with the latest edition of Building Regulations and carried out by a qualified electrician in accordance with the latest IEE Wiring Regulations. Before commencing any installation or maintenance work, ensure that the mains supply is switched off and the appropriate MCB or fuse is isolated.

MAINS WIRING Cable colours are shown opposite.



3 year warranty Rev A 10/5/2016



The Athena consists of two models, with integral PIR or without PIR. This luminaire is of Class II construction - Double insulated. IP 44 rated suitable for external applications. F marked, suitable for installation on to normal flammable surfaces. CE Approved. 180-240VAC supply.

7 watt LED—4200K—500 lm PIR detection range 110^o horizontal. When mounted between 1.8-2.5 m AGL detection range is 12m maximum (approx.)

LUX Level control: Adjusts from Daylight to Night.

Time Duration: Adjusts from 5 seconds to 5 minutes


W: www.diamondledlighting.co.uk E: sales@diamondledlighting.co.uk



Athena Bulkhead LED Instructions

IMPORTANT INSTALLATION INFORMATION This product must be installed in accordance with the latest edition of Building Regulations and carried out by a qualified electrician in accordance with the latest IEE Wiring Regulations. Before commencing any installation or maintenance work, ensure that the mains supply is switched off and the appropriate MCB or fuse is isolated.

MAINS WIRING Cable colours are shown opposite.





The Athena consists of two models, with integral PIR or without PIR. This luminaire is of Class II construction - Double insulated. IP 44 rated suitable for external applications. F marked, suitable for installation on to normal flammable surfaces. CE Approved. 180-240VAC supply.

7 watt LED—4200K—500 lm PIR detection range 110⁰ horizontal. When mounted between 1.8-2.5 m AGL detection range is 12m maximum (approx.)

LUX Level control: Adjusts from Daylight to Night.

Time Duration: Adjusts from 5 seconds to 5 minutes



W: www.diamondledlighting.co.uk E: sales@diamondledlighting.co.uk