

SPECIFICATION

Chatsworth II 4ft LED Non Corrosive

**Beam Angle**

120°

**Input**

220-240V

**Life Hours**

30,000

**Dimmable**

Available

**Colour Temperature**

5000K

	4ft Single	4ft Twin
Part Number	CH2-4SN	CH2-4TN
Wattage	20W	40W
Input Voltage	220-240V	220-240V
Beam Angle	120°	120°
Life Expectancy	30,000	30,000
Case	Polycarbonate	Polycarbonate
Colour Temperature	5000K	5000K
Output Lumens	2000lm	4000lm
Dimmable	Available	Available
Switch Time	15,000	15,000
Instant Light	Yes	Yes
CRI	>80	>80
IP Rating	IP65	IP65
Dimensions (mm)	1270 x 70 x 75	1270 x 110 x 72
Microwave	CH2-4SNMW	CH2-4TNMW
3Hr Emergency	CH2-4SNEM	CH2-4TNEM
3Hr Emergency & Microwave	CH2-4SNEMMW	CH2-4TNEMMW

Key Features

- Polycarbonate construction
- Plastic clips
- Suitable for indoor and outdoor use
- Complete with fixing accessories
- Available with corridor function exterior sensor
- 3 year warranty

CRI >80 **IP 65**

Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.

Tel: 01260 292 640 | Fax: 01260 279 116 | E-mail: sales@diamondledlighting.co.uk | Web: www.diamondledlighting.co.uk