

# Connectors



## CE-CONN2

2 Way Inline Connector  
 Terminals 3 LNE  
 Max Current 16A  
 Max Conductors 4mm<sup>2</sup>  
 Min Cable 7mm  
 Max Cable 13.5mm  
 Dimensions 81 x 24mm  
 IP rating IP68



## CE-TCONNECTOR

2 Way Inline Connector  
 Terminals 3 LNE  
 Max Current 16A  
 Max Conductors 4mm<sup>2</sup>  
 Min Cable 7mm  
 Max Cable 13.5mm  
 Dimensions 80 x 98mm  
 IP rating IP68



## NC-CIL3P

2 Way Inline Connector  
 With Lever Terminal block  
 Terminals 3 LNE  
 Max Current 16A  
 Min Conductors 0.5mm<sup>2</sup>  
 Max Conductors 2.5mm<sup>2</sup>  
 Dimensions 95 x 26mm  
 IP rating IP68



## NC-CIL5P

2 Way Inline Connector  
 With Lever Terminal block  
 Terminals 5 LNE BG  
 Max Current 16A  
 Min Conductors 0.5mm<sup>2</sup>  
 Max Conductors 2.5mm<sup>2</sup>  
 Dimensions 109 x 31mm  
 IP rating IP68



## NC-TC3P

3 Way Inline Connector  
 With Lever Terminal block  
 Terminals 3 LNE  
 Max Current 16A  
 Min Conductors 0.5mm<sup>2</sup>  
 Max Conductors 2.5mm<sup>2</sup>  
 Dimensions 117 x 73mm  
 IP rating IP68



## NC-FL34P

13 Pin Flow Connector  
 Terminals 3 - 4  
 Max Current 16A  
 Min Conductors 0.5mm<sup>2</sup>  
 Max Conductors 2.5mm<sup>2</sup>/4mm<sup>2</sup>  
 Dimensions 146 x 47 x 22mm  
 IP rating IP20



## NC-FL44P

4 Pin Flow Connector  
 Terminals 4 LNE +1  
 Max Current 16A  
 Min Conductors 0.5mm<sup>2</sup>  
 Max Conductors 2.5mm<sup>2</sup>/4mm<sup>2</sup>  
 Dimensions 146 x 50 x 25mm  
 IP rating IP20

**Please Note:** Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.