

# SPECIFICATION

## Moonstone

LED Panel (600 x 600mm)



**Beam Angle**  
120°



**Input**  
220-240V



**Life Hours**  
30,000



**Dimmable**  
Available



**Colour Temperature**  
4000K

Part Number	MS5-66NFF	MS5-66N5
Wattage	40W	40W
Input Voltage	220-240V	220-240V
Beam Angle	120°	120°
Life Expectancy	30,000	30,000
Case	PS & Aluminium Trim	PMMA & Aluminium Trim
Colour Temperature	4000K	4000K
Output Lumens	3400lm	3400lm
Dimmable	Available	Available
Switch Time	15,000	15,000
Instant Light	Yes	Yes
CRI	>80	>80
IP Rating	IP20	IP20
IK Rating	IK05	IK05
Dimensions (mm)	595 x 595 x 7.5	595 x 595 x 7.5
Warranty	2 years	5 years
Dimmable	MS5-66NFFD	MS5-66N5D
3Hr Emergency Kit	MS5-EM45W	MS5-EM45W
Surface Mount Kit	MS5-CWM	MS5-CWM

### Key Features

- Suspension Kit part number: **MS5-SUS**
- 3000K & 5750K options
- Available with a range of sensor options: Emergency, Microwave, Daylight Harvesting & Dimming
- RGB panels also available
- Panel available to meet UGR19 lighting schemes
- White & Silver Trim available



**Please Note:** Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications