

SPECIFICATION



Tatton Slimline 80W - 400W

High Power LED Floodlight



| Max Watts | 80W | 100W | 150W | 200W | 300W | 400W |
|-----------------------|----------------|----------------|----------------|----------------|----------------|----------------|
| Part Number | TA2-80C | TA2-100C | TA2-150C | TA2-200C | TA2-300C | TA2-400C |
| Part Number | | TA2-100W | TA2-150W | TA2-200W | TA2-300W | |
| Max Lumens | 8800 | 11000 | 16500 | 22000 | 33000 | 46000 |
| Operating Temperature | -20°C to +45°C | -20°C to +45°C | -20°C to +45°C | -20°C to +45°C | -20°C to +45°C | -20°C to +45°C |
| Switch Time | 12,500 | 12,500 | 12,500 | 12,500 | 12,500 | 15,000 |
| Instant Light | Yes | Yes | Yes | Yes | Yes | Yes |
| Dimensions (mm) | 303 x 356 x 70 | 303 x 356 x 70 | 364 x 421 x 70 | 364 x 421 x 70 | 429 x 471 x 70 | 599 x 442 x 62 |
| Weight (kg) | 3.08 | 3.08 | 4.71 | 4.755 | 6.185 | 8.1 |



Beam Angle
110°



Input
200-240V



Life Hours
25,000



Dimmable
No



Colour Temperature
3000K 6500K

Key Features

- Polycarbonate Front
- SMD LED with driver on board
- Angled bracket for easy installation
- Recommended for outdoor use
- Supplied with 1m cable
- 2 year warranty

CRI >80

IP 65



Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.

Tel: 01260 292 640 | Fax: 01260 279 116 | E-mail: sales@diamondledlighting.co.uk | Web: www.diamondledlighting.co.uk