

SPECIFICATION

Capri 3

Emergency LED Bulkhead



Beam Angle
50°



Input
220-240V



Life Hours
50,000



Dimmable
No



Colour Temperature
6500K



Part Number	CPEM3-M3	CPEM3-M3ST
Wattage	3.5W	3.5W
Version	Non Self Test	2 in 1 None Self Test & Self Test Switchable
Input Voltage	180-240V	180-240V
Type	Maintained	Maintained
Maintained Lumens	220lm	220lm
Discharge Lumens	130lm	130lm
CCT	4000K	4000K
Instant Light	Yes	Yes
IP Rating	IP65	IP65
Emergency Time	3 hours	3 hours
Battery	LiFePO4 1000mAh	LiFePO4 1000mAh
Dimensions (mm)	355 x 110 x 70	355 x 110 x 70
Recess Kit	CPEM3-REC	
Diffuser	CPEM3-DIF	

Key Features

- Suitable for maintained and non maintained applications
- White polycarbonate body and clear cover
- Supplied with legends
- Recess Kit **CPEM3-REC**
- Diffuser **CPEM3-DIF**
- 2 in 1 None Self Test & Self Test Switchable Version
- 5 Year Warranty



Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.