

SPECIFICATION



Alderley I

Selectable Power 4000K Asymmetric Flood Light



Beam Angle
150x80



Input
100-277V



Life Hours
50,000



Dimmable
No



Colour Temperature
4000K

| Part Number | AD1-120AT | AD1-240AT | AD1-500AT |
|---------------------------|-------------------|-------------------|-------------------|
| Power Range | 80W,100W,120W | 150W,200W,240W | 300W,400W,500W |
| Lumens | 12000lm - 18000lm | 22500lm - 36000lm | 45000lm - 75000lm |
| Max Power | 120W | 240W | 500W |
| Max Lumens | 18000lm | 36000lm | 75000lm |
| Switch Time | 25,000 | 25,000 | 25,000 |
| Instant Light | Yes | Yes | Yes |
| Operating Temp | -25°+50° | -25°+50° | -25°+50° |
| Beam Angle | 150x80° | 150x80° | 150x80° |
| Minimum Tilt Angle | 30° | 30° | 30° |
| Dimensions (mm) | 303 x 356 x 70 | 364 x 421 x 70 | 364 x 421 x 70 |

Key Features

- Selectable Power see table
- Up to 500W
- Angled bracket for easy installation
- Recommended for outdoor use
- 5 year warranty

CRI >80

IP 66



Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.

Tel: 01260 292 640 | Fax: 01260 279 116 | E-mail: sales@diamondledlighting.co.uk | Web: www.diamondledlighting.co.uk