

SPECIFICATION



Brightguard

ATEX Linear - Zone 2,22



Beam Angle
120°



Input
220-240V



Life Hours
50,000



Dimmable
Switch Dim / Dali Available



Colour Temperature
4000K Standard

Part Number	BRI2-5/4	BRI2-29/4	BRI4-29/4	BRI4-68/4	BRI4-44/4	BRI5-44/4	BRI5-74/4	BRI5-94/4	BRI5-115/4	BRI5-74/4	BRI5-95/4	BRI5-117/4
Size	2ft (670mm)	2ft (670mm)	4ft (1280mm)	4ft (1280mm)	5ft (1580mm)	5ft (1580mm)	5ft (1580mm)	5ft (1580mm)	5ft (1580mm)	5ft (1580mm)	5ft (1580mm)	5ft (1580mm)
Mounting Spacing	460mm	460mm	880mm	880mm	1000mm	1000mm	1000mm	1000mm	1000mm	1000mm	1000mm	1000mm
Aisle Optics										YES	YES	YES
Max Power	15W	29W	29W	58W	44W	74W	94W	115W	74W	95W	117W	117W
Max Lumen	2250	4350	4500	8700	6750	11150	13700	16350	11100	14950	17900	17900
Colour Temperature	4000K	4000K	4000K	4000K	4000K	4000K	4000K	4000K	4000K	4000K	4000K	4000K
Max Temp	60	55	60	40	55	45	40	40	45	50	40	40
Specifications	CCT: 3K, 4K, 5K											