

SPECIFICATION



Brightguard

ATEX Linear - Zone 2,22



Beam Angle
120°



Input
220-240V



Life Hours
50,000



Dimmable
Switch Dim / Dali Available



Colour Temperature
4000K Standard

Part Number	BRI2-15/4K	BRI2-29/4K	BRI4-29/4K	BRI4-58/4K
Size	2ft(670mm)	2ft(670mm)	4ft(1280mm)	4ft(1280mm)
Mounting	460mm	460mm	880mm	880mm
Max Power	15W	29W	29W	58W
Max Lum	2250	4350	4500	8700
Max Temp	60	55	60	40
Part Number	BRI5-44/4K	BRI5-74/4K	BRI5-94/4K	BRI5-115/4K
Size	5ft(1580mm)	5ft(1580mm)	5ft(1580mm)	5ft(1580mm)
Mounting	1000mm	1000mm	1000mm	1000mm
Max Power	44W	74W	94W	115W
Max Lum	6750	11150	13700	16300
Max Temperature	55	45	40	40
Part Number - Aisle Optics	BRI5A-74/4K	BRI5A-95/4K	BRI5A-117/4K	
Size	5ft(1580mm)	5ft(1580mm)	5ft(1580mm)	
Mounting	1000mm	1000mm	1000mm	
Max Power	74W	95W	117W	
Max Lum	11900	14950	17900	
Max Temp	45	50	40	

Key Features

- Low maintenance high output led light source
- certified by FTZU Ostrava-Radvanice
- certified type FTZU 16 ATEX 0102X
- Energy efficient control
- Reduced energy costs with motion sensor option
- Robust, Long Life Enclosure
- IP66, IK10 & Zone 2, 22
- Surface, Ceiling or Wall Mounted
- Screwless Three-Pole Terminal Block
- Available in 2ft to 5ft
- 5 Year Warranty