

SPECIFICATION



Phoenix Slim Pro Five Colour Tri Power

LED Bulkhead



Beam Angle
120°



Input
220-240V



Life Hours
50,000



Dimmable
No



Colour Temperature
2700K 3000K 4000K 5000K 6500K



Part Number	PHSP-18T
Selectable Wattage	8W 14W 16W
Input Voltage	220-240V
Case	Polycarbonate
Selectable Colour Temperature	2700K 3000K 4000K 5000K 6500K
Max Lumens	8W= 1000 14W=1650 16W=2000
Instant Light	Yes
IK Rating	IK08
Dimensions (mm)	Ø299 x 74
Emergency Module	PHP-PIEM
Microwave Corridor Module	PHP-PIMW
Microwave	PHSP-18TMW
3 Hr Emergency	PHSP-18TEM
3Hr Emergency AND Microwave	PHSP-18TEMMW
Photocell	PHSP-18TPC

Key Features

- Selectable 5 colour temperatures
- Conduit Entry
- Plug and Play Emergency and Microwave
- Emergency 3 Hour Maintained
- 3 Selectable power options
- Besa box mounting
- Replaces a 28W 2D
- 5 year warranty

CRI >80

IP 65



Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.