

SPECIFICATION



Rounded Trinity I Pro

3CCT - 4PWR - Batten



Beam Angle
120°



Input
220-240V



Life Hours
50,000



Dimmable
Inquire



Colour Temperature
3000K 4000K 6500K

	5ft	6ft
Part Number	RTR1P-5	RTR1P-6
Selectable Wattage	32W/40W/48W/56W	36W/46W/55W/62W
Max Lumens	8100	8900
Max Power	56W	62W
Dimensions (mm)	1462 x 62 x 74	1732 x 62 x 74
Plug in Microwave	LINP-PIMW	LINP-PIMW
Plug in 3hr Emergency	LINP-PIEM	LINP-PIEM
Fully Assembled Part No's		
Microwave	RTR1P-5MW	RTR1P-6MW
3Hr Emergency	RTR1P-5EM	RTR1P-6EM
3Hr Emergency & Microwave	RTR1P-5EMMW	RTR1P-6EMMW

Key Features

- Selectable 3CCT & 4 Power
- Plug in Internal Microwave/Corridor Function and 3hr Emergency
- Replace Single or Twin Battens
- BESA compatible
- Conduit Entry
- Steel and Polycarbonate Construction
- 5 year warranty



Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.

Tel: 01260 292 640 | Fax: 01260 279 116 | E-mail: sales@diamondledlighting.co.uk | Web: www.diamondledlighting.co.uk