

SPECIFICATION



2 in 1 DALI & PUSH

Dimming Driver



Part Number	ELED-40P-C300-1400DP2
Input Voltage	100~277VAC
Output Current	1400mA
Output Voltage	3-29
Frequency Range	47-63Hz
Inrush Current	5.68A (Twidth=7.2μs 230VAC)
Power Factor (Typ.)	0.97
AC Current (Typ.)	0.52A
Leakage Current	<0.50mA/220VAC
Operating Temperature	-40~80°C
Dimensions	171.5 x 54 x 20 mm

Key Features

- Constant current mode output with multiple levels selectable by dip switch
- DALI2 dimming function (IEC63286)
- Compatible with DALI and DALI2 dimming system
- AC input: 100-277VAC
- Built-in active PFC function
- Efficiency up to 86%
- Protections: Short circuit/ Over load/Over temperature
- Cooling by free air convection
- Suitable for intelligent LED lighting

IP 20

Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.

Tel: 01260 292 640 | Fax: 01260 279 116 | E-mail: sales@diamondledlighting.co.uk | Web: www.diamondledlighting.co.uk