



Triac Dimmable Driver



Part Number	ELED-40P-C300-1400T	ELED-60P-C600-2100T
Input Voltage	100-240V	100-240V
Frequency Range	47-63Hz	47-63Hz
Inrush Current	2.98A (Twidth=7.6 230VAC)	30.4A (Twidth=737 230VAC)
Power Factor (Typ.)	0.95	0.98
Full Load Efficiency (Typ.)	78%	83%
AC Current (Typ.)	0.15A	0.45A
Leakage Current	<0.50mA/220VAC	<0.50mA/220VAC

Key Features

- Constant current mode output with multiple levels selectable by dip switch
- Dimming function: Triac/phase cut dimming
- Work with leading or trailing edge Triac Dimmer
- *(On key: leading edge; 1 key: trailing)
- Built-in active PFC function
- Efficiency up to 80%
- Full protection plastic housing easy installation
- Cooling by free air convection
- Suitable for LED lighting and moving sign applications
- Strong compatibility, flicker-free dimming



Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.

Tel: 01260 292 640 | Fax: 01260 279 116 | E-mail: sales@diamondledlighting.co.uk | Web: www.diamondledlighting.co.uk