

SPECIFICATION

Fortress

ATEX High Bay - Zone 2,22,1



Beam Angle
55° i 94°



Input
230V



Colour Temperature
4000K or 5700K

Part Number (4000K)	FT1-90N	FT1-100N	FT1-150N
Part Number (5700K)	FT1-90C	FT1-100C	FT1-150C
Wattage	90W	100W	150W
Max Lumens	12800	16500	24700
Lumens Per Watt	142	165	165
Approx Weight (kg)	9	9	9
Operating Temperature	-40° To +40°	-40° To +40°	-40° To +40°
Dimension (mm)	317 x 317 x 84	317 x 317 x 84	317 x 317 x 84

Key Features

- Designed to work in zones 2, 21 & 22
- OBAC 24 ATEX 0435X certified
- IECEx OBAC 24.0005X certified
- Luminous efficacy up to 165 lm/W
- Lifetime up to 100 000 h (L80B10)
- Tempered glass for extra protection
- Easy installation and adjustment (mounting brackets included)
- Masking panel made to measure
- Can be adapted to any control system
- Dedicated optics with wide range of beam angle
- 5 Years Warranty



Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.

Tel: 01260 292 640 | Fax: 01260 279 116 | E-mail: sales@diamondledlighting.co.uk | Web: www.diamondledlighting.co.uk