

SPECIFICATION

Sentinel

ATEX Floodlight - Zone 2,22,1



Beam Angle
55°, 94°, 37°/103°



Input
230V



Colour Temperature
4000K or 5700K

Part Number	SNL1-400050N	SNL1-70N	SNL1-90N	SNL1-100N	SNL1-130N	SNL1-150N
Power (W)	50W	70W	90W	100W	130W	150W
Max Lumen	7100	10000	12800	16500	20800	24700
Lumen per Watt	142	143	142	165	160	165
Approx Weight (kg)	7	7	7	7	7	7
Operating Temperature	-40° To +60°	-40° To +60°	-40° To +60°	-40° To +60°	-40° To +60°	-40° To +60°
Dimensions (mm)	317 x 317 x 84	317 x 317 x 84	317 x 317 x 84	317 x 317 x 84	317 x 317 x 84	317 x 317 x 84

Key Features

- Designed to work in zones 2, 21 & 22
- OBAC 24 ATEX 0435X certified
- IECEx OBAC 24.0005X certified
- Luminous efficacy up to 165 lm/W
- Lifetime up to 100 000 h (L80B10)
- Three mounting methods (on handle, suspended, single-point)
- Equipped with tempered glass panel
- Easy assembly and setting (adjustable handle)
- Can be adapted to any control system
- 2 Year Warranty

CRI >70 **IP 66**

Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.

Tel: 01260 292 640 | Fax: 01260 279 116 | E-mail: sales@diamondledlighting.co.uk | Web: www.diamondledlighting.co.uk